

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number  
**WO 2005/040842 A1**

(51) International Patent Classification<sup>7</sup>: **G01R 33/12**

**GERSAK, Gregor** [SI/SI]; Opekarska 7, 1000 Ljubljana (SI). **KOBE, Spomenka** [SI/SI]; Ravnikova 8, 1001 Ljubljana (SI).

(21) International Application Number:  
PCT/EP2003/011086

(74) Agent: **GAGEL, Roland**; Landsberger Str. 480a, 81241 München (DE).

(22) International Filing Date: 7 October 2003 (07.10.2003)

(25) Filing Language: English

(81) Designated State (*national*): US.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(71) Applicant (*for all designated States except US*): **INSTITUTE JOZEF STEFAN** [SI/SI]; Jamova 30, 1001 Ljubljana (SI).

**Published:**  
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **MCGUINNESS, Paul, John** [GB/SI]; Zihherlova 8, 1001 Ljubljana (SI).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: PERMEATER FOR MEASURING MAGNETIC PROPERTIES AT HIGH TEMPERATURES

(57) Abstract: The present invention relates to a measuring tool for measuring magnetic properties of a magnetic sample in a closed loop, comprising an electromagnet (1) in a closed loop arrangement with two pole pieces (3) connected to a yoke (2), said pole pieces (3) forming a gap (4) for the placement of the sample (5), a search coil (6) for the measurement of a flux density B of the sample (5) and a magnetic field sensor (7) for the measurement of a magnetic field strength H in the gap (4) between said pole pieces (3). The pole pieces (3) comprise heater elements (8) for heating the pole pieces (3) to temperatures of at least 400° C and are thermally insulated against the yoke (2) of the electromagnet (1). The pole pieces (3), the search coil (6) and the magnetic field sensor (7) are made of materials which resist said high temperatures.



**WO 2005/040842 A1**